

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
0	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100

A method of manufacturing a molded product of a synthetic resin, characterized by comprising the steps of forming a container and a panel type surface layer member by subjecting a synthetic resin sheet to two-stage thermoforming; and forming an outer shell reinforcing layer on a rear surface of the surface layer member by subjecting a glass fiber-reinforced or non-glass-fiber-reinforced ABS resin or AS resin to injection molding, the method being capable of manufacturing molded products, such as a container and panels of a synthetic resin which have a strength and a rigidity high enough to withstand severe thermal resistance tests, a high quality and light weight, and which are capable of being obtained at a low cost and recycled easily.